



Body:

- Any of the 5 pre-painted bodies or clear body may be used (TRA10411). Bodies must remain clipless with stock mounting. Driver figure and rear spoiler must remain stock. Bracing is allowed to support body and aftermarket front nose body hold down is allowed.

•

Chassis:

- ONLY "BOX STOCK" Traxxas Modified chassis will be allowed.
- No aftermarket parts can be used.
- Transmission case must remain stock. NO plastic internal gears.
- 86 tooth stock spur gear must be used. 22-24 tooth pinion gears are allowed ONLY.

•

Electronics:

- ONLY "BOX STOCK" Traxxas Modified OEM electronics may be used. Traxxas BL-2S ESC part #3383, Traxxas BL-2S 3300KV brushless motor part #3384 (no motor tampering allowed, any motor modifications will result in immediate disqualification) and Traxxas stock 2075, 2075R or 2075X steering servo.
- Any ROAR legal 2S hard case battery that is 5500mah maximum capacity, any C rating and costs \$60 or less. Battery must remain in stock centered location.
- Any radio/receiver may be used.

Adjustments:

- Items you may adjust: Camber, front toe, ride height, shock oil, pistons, shock limiting, shock preload, factory shock locations and battery location front to rear.
- There is no weight rule.

Suspension:

- Stock Traxxas Modified shocks must be used (Any of the 5 colors allowed). Front bodies and shafts stay in front and rear bodies and shafts stay in rear.
- Only original Traxxas Modified springs may be used. Front spring part #5434 and rear spring part #5434.

Tires & Wheels:

- Traxxas Modified box stock tires (Part #10470 & 10471 unmounted and 10473 mounted) may be used. No softening, tire doping, grinding or grooving of any kind allowed.
- Aftermarket closed cell foam inserts are allowed.
- Tires may be cleaned with water or Simple Green ONLY!

Common Sense:

- If these rules do not specifically say you CAN do it, you CANNOT!!! Period!!!